AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A structure control method comprising:

measuring a first Raman spectrum of a mixture of nano-scale low-dimensional quantum structures of differing densities of states at a wavelength of an electromagnetic wave with which the mixture of nano-scale low-dimensional quantum structures of differing densities of states is irradiated;

irradiating the mixture of nano-scale low-dimensional quantum structures of differing densities of states with the an electromagnetic wave in air for two hours after measuring the first Raman spectrum, the electromagnetic wave having an energy density of 10 kW/cm² so as to selectively oxidize and remove a low-dimensional quantum structure of a density of states resonating with the wavelength of the electromagnetic wave;

measuring a second Raman spectrum of the irradiated mixture of nano-scale low-dimensional quantum structures at the wavelength of the electromagnetic wave; and

measuring a reduction in peak intensity of the second Raman spectrum to confirm the selective oxidation <u>and removal from the mixture</u> of the low-dimensional quantum structure.

2. (Cancelled)

3. (Previously Presented) The structure control method as set forth in claim 1, wherein the low-dimensional quantum structures comprise nanotubes or nanoparticles.

U.S. Application No. 10/569,548 Atty. Dkt. No. 12480-000162/US

4. (Previously Presented) The structure control method as set forth in

claim 1, wherein the low-dimensional quantum structures comprise carbon or boron

nitride.

5. (Previously Presented) The structure control method as set forth in

claim 1, wherein the low-dimensional quantum structures have a single-walled

structure.

6. (Previously Presented) The structure control method as set forth in

claim 1, wherein the electromagnetic wave is a laser beam.

7. (Withdrawn) A producing method of a nano-scale low-dimensional

quantum structure, comprising the step of irradiating a mixture of nano-scale low-

dimensional quantum structures of differing densities of states with an

electromagnetic wave in an oxygen atmosphere, so as to selectively oxidize a low-

dimensional quantum structure of a density of states resonating with the

electromagnetic wave and thereby remove a structure with the density of states

resonating with the electromagnetic wave.

8. (Withdrawn) A producing method of a nano-scale low-dimensional

quantum structure, comprising the step of irradiating a mixture of nano-scale low-

dimensional quantum structures of differing densities of states with an

electromagnetic wave in an oxygen atmosphere, so as to selectively oxidize a low-

dimensional quantum structure of a density of states resonating with the

3

electromagnetic wave and thereby retain a structure with a density of states not resonating with the electromagnetic wave.

9-10. (Cancelled)

11. (Previously Presented) The structure control method as set forth in claim 3, wherein the nanotubes or nanoparticles comprise carbon or boron nitride.

12. (Cancelled)

- 13. (Previously Presented) The structure control method as set forth in claim 3, wherein the nanotubes or nanoparticles have a single-walled structure.
- 14. (Previously Presented) The structure control method as set forth in claim 4, wherein the low-dimensional quantum structures have a single-walled structure.

15. (Cancelled)

- 16. (Previously Presented) The structure control method as set forth in claim 3, wherein the electromagnetic wave is a laser beam.
- 17. (Previously Presented) The structure control method as set forth in claim 4, wherein the electromagnetic wave is a laser beam.

18. (Previously Presented) The structure control method as set forth in claim 5, wherein the electromagnetic wave is a laser beam.

19-20. (Cancelled)